
Declarative Stream Mapping (DSM) Documentation

Release 1

Mehmet Fatih Ercik

Jun 14, 2023

QUICK START GUIDE:

1	Introduction	1
2	Simple Example	3
3	Features	7
4	Installation	9
5	Sample Config File	11
6	Introduction	13
7	Definitions	15
8	Format	17
9	Document Structure	19
10	Schema	21
10.1	DSM Object	21
10.1.1	params	22
10.1.2	transformations	22
10.1.3	functions	23
10.1.4	fragments	23
10.1.5	result	24
10.1.6	\$Extends	25
10.2	Parsing Element Object	26
10.2.1	fieldName	28
10.2.2	dataType	28
10.2.3	dataTypeParams	30
10.2.4	type	30
10.2.4.1	std	31
10.2.4.2	object	31
10.2.4.3	array	32
10.2.4.4	sum	33
10.2.4.5	multiply	34
10.2.4.6	divide	36
10.2.4.7	join	37
10.2.5	typeParams	38
10.2.6	path and parentPath	39
10.2.7	fields	42

10.2.7.1	Type of Value Definition	42
10.2.8	filter	44
10.2.9	default	46
10.2.10	transformationCode	47
10.2.11	function	48
10.2.12	uniqueName	49
10.2.13	normalize	51
10.2.14	xml	51
10.2.15	\$ref	51
10.3	Transformation Element Object	54
10.4	Default Object	55
10.4.1	value	55
10.4.2	force	55
10.4.3	atStart	55
10.5	XML Object	56
10.5.1	attribute	56
11	Absolute Path	59
12	Expressions and Scripting	63
12.1	Loading Time Expression	63
12.1.1	Example	64
12.2	Parsing Time Expression	65
12.2.1	all	66
12.2.2	self	68
12.2.3	Example	68
13	Merge of DSM Document	71
14	Property Assignment Order	75
15	Indices and tables	85

**CHAPTER
ONE**

INTRODUCTION

Declarative Stream Mapping(DSM) is a *stream* deserializer library that makes parsing of **XML and JSON** easy. DSM allows you to make custom parsing, filtering, transforming, aggregating, grouping on any JSON or XML document at stream time(read only once). DSM uses yaml or json for configuration definitions

If you parsing a complex, huge file and want to have high performance and low memory usage then DSM is for you.

CHAPTER TWO

SIMPLE EXAMPLE

Lets Parse below simple JSON and XML file with DSM

File contents are taken from [Swagger Petstore example](#). Slightly changed.

Source file

JSON

```
"id" 1
"name" "Van Kedisi"
"status" "sold"
"createDate" "01/24/2019"
"category" "id" 1 "name" "Cats"
"tags"
    "id" 1 "name" "Cute"
    "id" 2 "name" "Popular"

"photoUrls" "url1" "url2"
```

XML

```
<?xml version="1.0" encoding="UTF-8" ?>

<Pet id="1">
    <name>Van Kedisi</name>
    <status>sold</status>
    <createDate>01/24/2019</createDate>
    <category>
        <id>1</id>
        <name>Cats</name>
    </category>
    <tags>
        <tag>
            <id>1</id>
            <name>Cute</name>
        </tag>
        <tag>
            <id>2</id>
            <name>Popular</name>
        </tag>
    </tags>
</Pet>
```

(continues on next page)

(continued from previous page)

```

</tags>
<photoUrls>
    <photoUrl>url1</photoUrl>
    <photoUrl>url2</photoUrl>
</photoUrls>
</Pet>

```

Those are rules that we want to apply during parsing.

- exclude “photoUrls” tag.
- read only “name” field of “tags” tag.
- read only “name” field of “category” tag.
- add new the “isPopular” field that it’s value is true, if “tag.name” has “Popular” value

DSM config file

[YAML]

```

params
  dateFormat
result

xml
  path
filter
fields
  id
  dataType
  xml
    attribute
  name
  status
  createDate
  category
    path
  isPopular
    default
tags

  ↵ # this is a regex expression. works for both JSON and XML

```

Class to deserialize

[JAVA]

```

public class
  private int
  private
  private boolean
  private
  private

```

(continues on next page)

(continued from previous page)

```
private  
private  
  
// getter/setter
```

Read Data

```
        new          "dsm-config-file.yaml"  
        setType      XML create  
        toObject new  "path/to/xmlFile.xml"    class  ↴  
↳ // read data from xml file  
  
        setType      JSON create  
        toObject new  "path/to/jsonFile.json"   class  ↴  
↳ // read data from json file
```

CHAPTER
THREE

FEATURES

- **Work** for both **XML** and **JSON**
- **Custom stream parsing**
- **Filtering** by value on any field with **very low cognitive complexity**
- Flexible value **transformation**.
- **Default value assignment**
- Custom **function calling** during parsing
- **Powerful Scripting**([Apache JEXL](#), Groovy, Javascript and other jsr223 implementations are supported)
- **Multiple inheritance** between DSM config file (DSM file can **extends to another config file**)
- **Reusable fragments support**
- **Very short learning curve**
- **Memory** and **CPU** efficient
- **Partial data extraction** from JSON or XML
- **String manipulation** with expression

CHAPTER
FOUR

INSTALLATION

Maven

Jackson

```
<dependency>
  <groupId>com.github.mfatihercik</groupId>
  <artifactId>dsm</artifactId>
  <version>1.0.4</version>
</dependency>
```

Gradle

Jackson

```
compile ('com.github.mfatihercik:dsm:1.0.4')
```

CHAPTER
FIVE

SAMPLE CONFIG FILE

Detailed documentation and all option is [here](#).

This config file contains some possible option and their short description.

[header.yaml]

```
params
    dateFormat                                # define date format for "date" data type
transformations
    SOLD_STATUS
    ↳ # value transformation for "isAvailable" property
        map
            sold
            pending
            available
            DEFAULT
    SOLD_STATUS_SKIP
        $ref                                     # extends to "SOLD_STATUS" transformation.
        map
            DEFAULT                               # exclude default value
            onlyIfExists
    ↳ # make transformation only source value exist in transformation map other wise return as it is
functions
    insertPet
    ↳ # declare a function to declare at Parsing Element.

fragments
    category                                    # create reusable fragment

        id
        name
        type
```

[main.yaml]

```
$extends
result                                         # extends to header.yaml config.

path                                           # result is an array
    ↳
    # start reading form beginning for json. path is a regex. we can define both for xml and json same time
    xml
```

(continues on next page)

(continued from previous page)

```

path                                # start reading from /Pets/Pet for xml

filter
# filter by "isAvailable" property. "self" key word refers to current Node. self.parent refers to parent

function
# call "insertPet" function for every element of "result" array

fields
name                               # read name as string.
id
dataType
xml
attribute                           # id is an attribute on /Pets/Pet tag.
createDate

# use dateFormat in params then convert string to date

isAvailable
path                                # read isAvailable as string from "status" tag
dataType
transformationCode

# user "SOLD_STATUS" transformation to map from "status" to "isAvailable"
category
$ref
fields
type

# exclude "type" field from "category" fragment
name
default  'Animal'

#set default value to 'Animal' if "category/name" tag not exist in source document
isPopular
default

# set default value of "isPopular" property

tags

filter                                # filter by length of value.
xml
path

```

**CHAPTER
SIX**

INTRODUCTION

Declarative Stream Mapping(DSM) is a stream deserializer library that works for both XML and JSON. DSM allows you to make custom parsing, filtering, transforming, aggregating, grouping on any JSON or XML document at stream time(read once). There is no need to writing custom parser. DSM use yaml or json configuration file to parse data. Processed data can be deserialized to java classes.

**CHAPTER
SEVEN**

DEFINITIONS

DSM Document:

A document (or set of documents) that defines or describes parsing element definition uses and conforms to the DSM Specification.

Source Document:

Document(File, Stream, String, HTTP Request Payload) contains JSON or XML data.

**CHAPTER
EIGHT**

FORMAT

DSM document is a JSON object, which maybe represented either in JSON or YAML format. All field names in the specification are case sensitive. This includes all fields that are used as keys in a map, except where explicitly noted that keys are case insensitive.

**CHAPTER
NINE**

DOCUMENT STRUCTURE

DSM document may be made up single document or divided into multiple connected parts at the discretion of the user. In later case, *\$extends* fields must be used to reference those parts.

In the following description, if a field is not explicitly REQUIRED or described with a MUST or SHALL, it can be considered OPTIONAL.

10.1 DSM Object

This is the root document object of the DSM document.

Fields:

Field Name	Type	Description
version	string	REQUIRED. This string MUST be the semantic version number of the DSM Specification version that the DSM document uses. The DSM field SHOULD be used by tooling specifications and clients to interpret the DSM document
params	Map[string,any]	params_ field is a map that contains parameter definition to configure DSM document and `Parsing Element`_s.
transformations	Map[string,`Transformation Element`_]	Declaration of Map contains <i>transformationCode</i> as key, and <i>Transformation Element</i> holds lookup table to transform value from <i>Source Document</i> to destination document.
functions	Map[string,Function]	Declaration of Map contains <i>function</i> name as key, and <i>function deceleration</i> as value. functions are used for custom parsing or calling services with parsed data. Functions implements FunctionExecutor interface.
fragments	Map [String, Parsing Element]	A map contains declaration of reusable <i>Parsing Element</i> . The fragment definition can be referenced with \$ref_ field while defining <i>Parsing Element</i> .
result	Parsing Element	REQUIRED. The entry point of <i>Parsing Element</i> declarations. The result field defines structure of the output.
\$extends	string	`\$extends`_ field is used for import external DSM document.

10.1.1 params

`params` field is a map that contains parameter definition to configure DSM document and *Parsing Element*. The key of params map is string and case sensitive. The value of params map can be any type of json object(int, boolean, object, array) accepted by JSON and YAML specification.

Example DSM document that contains params.

YAML

```
version
params
  dateFormat
  rootPath
  category
    foo
  acceptedCountryCode  TR US FR
```

JSON

```
"version"  1.0
"params"
  "dateFormat"  "dd.MM.yyyy"
  "rootPath"  "fooBar/foo"
  "category"
    "foo"  "bar"

  "acceptedCountryCode"  "TR"  "US"  "FR"
```

10.1.2 transformations

Deceleration of Map contains *transformationCode* as key, and *Transformation Element* as value. *Transformation Element* holds lookup table to transform value from *Source Document* to destination document.

Example CF document that contains transformations

YAML

```
version
transformations
  COUNTRY_CODE_TO_NAME
    map
      DEFAULT
      TR
      US
```

JSON

```

"version" 1.0
"transformations"
  "COUNTRY_CODE_TO_NAME"
    "map"
      "TR" "Turkey"
      "US" "United States"
      "DEFAULT" "Other"

```

10.1.3 functions

Deceleration of Map contains *function* name as key, and *function deceleration* as value. functions are used for custom parsing or calling services with parsed data. Functions implements FunctionExecutor interface.

Example CF document that contains functions

YAML

```

version
functions
  insertProduct
  approveOrder

```

JSON

```

"version" 1.0
"functions"
  "insertProduct" "com.example.InsertProduct"
  "approveOrder" "com.example.ApproveOrder"

```

10.1.4 fragments

A map contains declaration of reusable *Parsing Element*. The fragment definition can be referenced with *\$ref* field while defining *Parsing Element*.

Example CF document that contains functions

YAML

```
version
fragments
  product
    fields
      id
      name
      price
```

JSON

```
"version" 1.0
"fragments"
  "product"
    "fields"
      "id" "string"
      "name" "double"
      "price" "double"
```

10.1.5 result

REQUIRED. The entry point of *Parsing Element* declarations. The result field defines structure of the output.

Example CF document that contains result

YAML

```
version
result
  type
  path
  fields
    id
    name
    price
```

JSON

```
"version" 1.0
"result"
  "type" "object"
  "path" "/"
  "fields"
    "id" "string"
```

(continues on next page)

(continued from previous page)

```
"name" "double"
"price" "double"
```

10.1.6 \$extends

\$extends field is used for import external DSM document to current DSM document. its value is basically relative path or URI definition of external DSM document. if its value start with “\$” sing, it is accepted as an *expression* and resolved by expression resolver. External DSM document will *merged* into current DSM document. \$extends can also be list of path or URI. *Merge* process start from first element to last element. Firstly current DSM document *merged* with first element then result of *merge* process extended to second element etc..

Example CF document that contains extends

YAML

```
version
$extends
```

or

```
version
params
  rootPath
$extends
```

JSON

```
"version" 1.0
"$extends" "/foo/bar/external.json"
```

or

```
"version" 1.0
"params"
"rootPath" "/bar/foo/"

"$extends" "/foo/bar/external.json" "$params.rootPath.concat(
  ↵'externalWithExpression.json')"
```

10.2 Parsing Element Object

Parsing Element is basic object of DSM. Parsing Element contains set of rules for parsing specific tag of *Source Document*

Fields:

Field Name	Type	Description
<i>field-Name</i>	string	REQUIRED <i>fieldName</i> define the name of the property to expose by current object. the <i>fieldName</i> is unique in object.
<i>dataType</i>	string	REQUIRED . The data type of exposed field. it may have extra parameter provided with <i>dataTypeParams</i>
<i>dataType-Params</i>	Map[string,any]	extra parameters for dataType field need to convert. for example. dateFormat for dataType
<i>type</i>	string	the name of the parsing strategy for the current field. the default is STD.
<i>type-Params</i>	Map[string,any]	it is used for passing extra parameter to <i>dataType</i> converter. <i>type-Params</i> field <i>extended</i> to <i>params</i> field.
<i>path</i>	string	The path field specifies the location of a tag in the <i>source document</i> relative to the path field of the higher-level Parsing Element definition. The default value is the value in the <i>fieldName</i> field.
<i>parent-Path</i>	string	The <i>parentPath</i> field is used in a slightly more complex parsing definitions. it holds path to parent tag of the tag specified in the “ <i>path</i> ” field.
<i>default</i>	string,`Default Object`_	default value of the field if <i>path</i> not exist in the source document. if default value starts with “\$” character it is accepted as <i>expression</i> and it is resolved by expression resolver.
<i>filter</i>	string	The Filter field determines whether the value of a <i>Parsing Element Object</i> (complex or simple <i>type</i> does not matter) is added to the object tree. The filter field is an <i>expression</i> that returns true or false.
<i>transformation-Code</i>	string	this field refers to the definition of the transformation to be used to transform the tag value.
<i>function</i>	string	name of the function in <i>functions</i> map.
<i>normalize</i>	string	this field is used to normalize the value of tag . It is an expression.
<i>unique-Name</i>	string	When “ <i>fieldName</i> ” fields of complex <i>Parsing Element</i> definitions are the same in the DSM document, these definitions are differentiated by using the “ <i>uniqueKey</i> ” field.
<i>xml</i>	Map[string,any]	XML related configuration goes under this tag.
<i>at-tribute</i>	boolean	it is indicates that the current <i>Parsing Element Object</i> is an attribute on the tag pointed to by the <i>parentPath</i> field in the <i>xml</i> .
over-write-ByDefault	boolean	force using <i>default</i> field. Mostly used with filter field.
<i>fields</i>	Map[string, String] - Parsing Element Object - [Parsing Element Object]]	fields of the current object. its only valid for object and array <i>type</i>
<i>\$ref</i>	string	\$ref_ field is used to <i>extends</i> current config to given fragment . it's value is an expression.

10.2.1 fieldName

REQUIRED The `fieldName` define the name of the property to expose by current object. the `fieldName` is unique in object.. However, a `fieldName` may have multiple *Parsing Element*. The `fieldName` is not explicitly defined. it is defined with `fields` property. The keys of `fields` map are the `fieldName` of the Parsing Element.

In blow DSM document, id, name, and price are `fieldName` of the result object. The `result` object exposes id, name and price property

YAML

```
result          # fieldName is result
version

fields
  id          # fieldName is id
  price
  name        # fieldName is name
```

JSON

```
"version": 1.0
"result":
  "type": "object"
  "path": "/"
  "fields":
    "id": "string"
    "name": "double"
    "price": "double"
```

10.2.2 dataType

The `dataType` field defines data type (string, int, boolean etc.) of the exposed property. it is basicity a converter from string to given `dataType` type. it may need extra parameters to convert a string to given data `dataType`. Extra parameters may be provided with `params` or `dataTypeParams`.

Supported `dataType` name and their corresponding java class:

Type Name	Java Type	Extra Parameters
int	int	
float	float	
short	short	
double	double	
long	long	
date	date	dateFormat(required)
boolean	boolean	
char	char	
BigDecimal	BigDecimal	
BigInteger	BigInteger	

YAML

```

version
params
  dateFormat          # default 'dateFormat' for all 'date' dataType
result

fields
  id
  name               # implicitly defined dataType. dataType is string
  price
    dataType         # explicitly defined dataType dataType. type is double
  createDate
  modifiedTime
    dataType
  # implicitly defined the date dataType. and 'dateFormat' is defined in params field.
  dataTypeParams
    dateFormat      "yyyy-MM-dd'T'HH:mm:ss'Z'"
# explicitly defined the date dataType. and 'dateFormat' is defined in dataTypeParams field.

```

JSON

```

"version": 1.0
"params":
  "dateFormat": "dd.MM.yyyy"

"result":
  "type": "object"
  "path": "/"
  "fields":
    "id": "string"
    "name": "double"
    "price":
      "dataType": "double"

    "createDate": "date"
    "modifiedTime":
      "dataType": "date"

```

(continues on next page)

(continued from previous page)

```
"dataTypeParams"
  "dateFormat" "yyyy-MM-dd'T'HH:mm:ss'Z'"
```

10.2.3 dataTypeParams

`dataTypeParams` is used for passing extra parameters to a `dataType` convert. `dataTypeParams` field *extended* to `params` field.

Check [example](#) here.

10.2.4 type

`type` defines how tags in the source document are parsed. it also defines the structure of the output object and hierarchy of the object tree. it may need extra parameters. Extra parameters are provided with `typeParams` field that *extended* to `params` field. Basically, there are two main “type” categories which are “complex”, and “simple”. The complex category includes “tagTypes” which exposes complex data `dataType` such as object or arrays. the simple category includes tagTypes which expose data type in the `dataType` field.

Supported `type`'s:

Type Name	Category	Java Type	Extra Parameters
<code>std</code>	Simple	<code>dataType</code>	default <code>type</code> if not defined explicitly
<code>object</code>	Complex	Map	
<code>array</code>	Complex	List<Map> List< <code>dataType</code> >	-
<code>sum</code>	Simple	<code>dataType</code>	fields: array of fieldName of current object.
<code>multiply</code>	Simple	<code>dataType</code>	fields: array of fieldName of current object.
<code>divide</code>	Simple	<code>dataType</code>	fields: array of fieldName of current object.
<code>join</code>	Simple	<code>dataType</code>	fields: array of fieldName of current object, separator : separator string. default is comma(,)

10.2.4.1 std

std is basic *type* which copy the value of the tag in the source document to the current object. std is the default value of the *type* field. Data *dataType* is defined in **dataType_ype_** field.

YAML

```
version
result
  type
  path
  fields
    foo      # tag type is STD
    bar      # tag type is STD
```

JSON

```
"version" 1.0
"result"
  "type" "object"
  "path" "/"
  "fields"
    "foo" "string"
    "bar" "int"
```

10.2.4.2 object

object *type* is used to expose an object. *Parsing Element* which has “object” *type* must have ‘*fields*’ field.

YAML

```
version
result
  type
  path
  fields
    id
    name
    price
```

JSON

```
"version" 1.0
"result"
  "type" "object"
```

(continues on next page)

(continued from previous page)

```
"path" "/"
"fields"
  "id" "string"
  "name" "string"
  "price" "double"
```

Above DSM document generate following output(values are only example) :

```
"id" "11111"
"name" "foo"
"price" 1111.111
```

10.2.4.3 array

array *type* is used to expose an array. Items of the array may be a object or simple *dataType*. if *Parsing Element* has “*fields*” field then the array *type* exposes List<Object>. if *fields* field is not defined, the data type of array item decided *dataType* field.

YAML

```
version
result
  type      # EXPOSE [Object] array of Object
  path
  fields
    id
    name
    price
    tags      # EXPOSE [string] array of string
    type
    path
    type
```

JSON

```
"version" 1.0
"result"
  "type" "object"
  "path" "/"
  "fields"
    "id" "string"
    "name" "string"
    "price" "double"
    "tags"
```

(continues on next page)

(continued from previous page)

```

"type" "array"
"path" "tag"
"type" "string"

```

Above DSM document generate following output(values are only example) :

```

"id" "11111"
"name" "foo"
"price" 1111.111
"tags" "foo" "bar"

```

10.2.4.4 sum

sum type is used to sum properties defined with “fields” in **typeParams_**. if one of the properties that defined in *fields* does not exist in the current object, it is accepted as ZERO.

if current property(*Parsing Element* that “*sum*” *type* is defined on) is defined in “fields” in **typeParams_**, current property value is added to total result.(sum with self)

(Explained with example below)

typeParams:

Name	Type	Description
fields	array	REQUIRED list of <i>fieldName</i> of the properties in parent <i>Parsing Element</i> to sum.

YAML

```

version
result
  type
  path
  fields
    foo
    bar
    fooAndBar
      path      # when current object closed
      type     # declare sum type to sum foo and bar field
    typeParams
      ↳ # sum foo, and bar fields then set to fooAndBar property of current object.
      sumWithSelf
        type      # declare sum type to sum foo and bar field

```

(continues on next page)

(continued from previous page)

```

typeParams

→ # sum foo, bar and sumWithSelf(current field) fields then set sumWithSelf to total property of current

```

JSON

```

"version" 1.0
"result"
  "type" "object"
  "path" "/"
  "fields"
    "foo" "int"
    "bar" "int"
    "fooAndBar"
      "path" "\."
      "type" "sum"
      "typeParams"
        "fields" "foo" "bar"

    "sumWithSelf"
      "type" "sum"
      "type" "int"
      "typeParams"
        "fields" "foo" "bar" "sumWithSelf"

```

10.2.4.5 multiply

multiply type is used to multiply properties defined with “fields” in **typeParams_**. if one of the properties that defined in *fields* does not exist in the current object, it is accepted as ONE.

if current property(*Parsing Element* that “multiply” *type* is defined on) is defined in “fields” in **typeParams_**, current property value is multiplied with total result. (multiply with self)

(Explained with example below)

typeParams:

Name	Type	Description
fields	array	REQUIRED list of field name of the properties in current object to multiply.

YAML

```

version
result
  type
  path
  fields
    foo
    bar
    fooAndBar
      path      # when current object closed
      type      # declare multiply type to sum foo and bar field

      typeParams
      ↳
      ↳ # multiply foo, and bar fields then set it to fooAndBar property of current object.

      multiplyWithSelf
        type      # declare multiply type to sum foo and bar field

        typeParams
        ↳
        ↳ # multiply foo, bar and multiplyWithSelf(current field) fields then set it to multiplyWithSelf proper

```

JSON

```

"version" 1.0
"result"
  "type" "object"
  "path" "/"
  "fields"
    "foo" "int"
    "bar" "int"
    "fooAndBar"
      "path" "\."
      "type" "multiply"
      "typeParams"
        "fields" "foo" "bar"

    "multiplyWithSelf"
      "type" "multiply"
      "type" "int"
      "typeParams"
        "fields" "foo" "bar" "multiplyWithSelf"

```

10.2.4.6 divide

divide type is used to divide properties defined with “fields” in **typeParams_**. if one of the properties that defined in *fields* does not exist in the current object, it is accepted as ONE.

if current property(*Parsing Element* that “divide” *type* is defined on) is defined in “fields” in **typeParams_**, current property value is divided with total result. (divide with self)

(Explained with example below)

typeParams:

Name	Type	Description
fields	array	REQUIRED list of field name of the properties in current object to divide.

YAML

```

version
result
  type
  path
  fields
    foo
    bar
    fooAndBar
      path      # when current object closed
      type      # declare divide type to sum foo and bar field

    typeParams

  ↵# divide foo with bar (foo/bar) fields then set it to fooAndBar property of current object.
  divideWithSelf
    type      # declare divide type to sum foo and bar field

    typeParams

  ↵# divide foo with bar then divide with divideWithSelf(current field) (foo/bar/divideWithSelf) fields

```

JSON

```

"version": 1.0
"result"
  "type": "object"
  "path": "/"
  "fields"
    "foo": "int"
    "bar": "int"
    "fooAndBar":
      "path": "\."
      "type": "divide"
      "typeParams"
        "fields": "foo", "bar"

```

(continues on next page)

(continued from previous page)

```

"divideWithSelf"
  "type"  "divide"
  "type"  "int"
  "typeParams"
    "fields"  "foo"  "bar"  "divideWithSelf"

```

10.2.4.7 join

join type is used to join properties defined with “fields” in **typeParams_**. if one of the properties that defined in *fields* does not exist in the current object, it is skipped.

if current property(*Parsing Element* that “join” *type* is defined on) is defined in “fields” in **typeParams_**, current property value is included in to joining (join with self) Values are separated by *separator* defined in “*typeParams*”. The default separator is a comma(,)

typeParams:

Name	Type	Description
fields	array	REQUIRED list of field name of the properties in current object to join.
separator	string	separator string. default is comma(,)

YAML

```

version: 1.0
result:
  type: object
  path: /
  fields:
    foo: string
    bar: string
    fooAndBar:
      path: \. # when current object closed
      type: join # declare join type to sum foo and bar field
      type:int
      typeParams:
        fields:[foo,bar] # join foo and bar (foo,bar) fields then set it to
        ↵fooAndBar property of current object.
      joinWithSelf:
        type: join # declare join type to sum foo and bar field
        type:int
        typeParams:
          separator: &
          fields:[foo,bar,sumWithSelf] # join foo,bar, and joinWithSelf(current

```

(continues on next page)

(continued from previous page)

```
↳ field) (foo&bar&joinWithSelf) fields then set it to joinWithSelf property of current ↳ object.
```

JSON

```
"version" 1.0
"result"
  "type" "object"
  "path" "/"
  "fields"
    "foo" "string"
    "bar" "string"
    "fooAndBar"
      "path" "\."
      "type" "join"
      "typeParams"
        "fields" "foo" "bar"

    "joinWithSelf"
      "type" "join"
      "type" "int"
      "typeParams"
        "separator" "&"
        "fields" "foo" "bar" "joinWithSelf"
```

10.2.5 typeParams

typeParams is used for passing extra parameters to *type* field. The typeParams field is *extended* to *params* field.

Examples:

YAML

```
version
result
  type
  path
  fields
    foo
    bar
    fooAndBar
      path      # when current object closed
      type     # declare join type to concat foo and bar field
```

(continues on next page)

(continued from previous page)

typeParams	<i># typeParams is used to pass fields parameter to type</i>
-------------------	--

JSON

```

"version" 1.0
"result"
  "type" "object"
  "path" "/"
  "fields"
    "foo" "string"
    "bar" "string"
    "fooAndBar"
      "path" "\."
      "type" "join"
      "typeParams"
        "fields" "foo" "bar"
  
```

10.2.6 path and parentPath

The path and parentPath fields indicate which tags are used in the *source document* during parsing. The value of those fields are regular expressions.

The **path** field specifies the location of a tag in the *source document* relative to the path field of the higher-level *Parsing Element* definition. The default value is the value in the *fieldName* field.

The **parentPath** field is used in a slightly more complex parsing definitions. it holds path to parent tag of the tag specified in the “path” field.

The *path* and *parentPath* fields can be defined as the relative path as in unix. Relative paths are resolved according to the structure in the DSM document, not by the structure in the source file.

Some example of relative path:

```

current
./

parent
../

parentOfParent
 ../../

categoryInParent
./category

categoryInCurrent
./category
  
```

To find the exact tag path for the current *Parsing Element*, starting from the result field, all the *parentPath* and *path* fields from top to bottom are merged with the “/” character.

tagParentAbsolutePath and **tagAbsolutePath** evaluated as follow:

currentObject mean is *Parsing Element* that current path and parentPath is defined **parentObject** mean is parent *Parsing Element* of currentObject

- parentObject = if (**parentPath+path**) is relative path then find parentObject by resolving relative path else currentObject.parent
- **tagParentAbsolutePath** = parentObject.path+”/”+currentObject.parentPath
- **tagAbsolutePath** = absoluteParentPath+”/”+currentObject.path

if **tagAbsolutePath** regex match any *absolute* path of tag, value of this tag evaluated by *type*

To explain with example:

```

result
  path                                #path = orders/order
                                         #parentPath = ""
                                         #tagAbsolutePath= /orders/order
                                         #tagParentAbsolutePath= /
fields
  defaultName
  ↵#path = defaultName (default value is fieldName)           #parentPath = ""
  ↵#tagParentAbsolutePath =/orders/order (parent(result) absoluteTagPath))           ↵
  ↵#tagAbsolutePath =/orders/order/defaultName
    tagPathDefined
      path                                #path =status
                                         #parentPath = ""
  ↵#tagParentAbsolutePath =/orders/order (parent(result) absoluteTagPath))           ↵
  ↵#tagAbsolutePath =/orders/order/status
    tagPathAndParentPath
      path                                #path = name
      parentPath                         #parentPath = category
  ↵#tagParentAbsolutePath =/orders/order/category
  ↵#tagAbsolutePath =/orders/order/category/name
innerObject
  type
  path                                #path = "innerObject"
                                         #parentPath = ""
  ↵#tagParentAbsolutePath =/orders/order
  ↵#tagAbsolutePath =/orders/order/innerObject
    fields
      normalPathInInnerObject          #path = "normalPathInInnerObject"

```

(continues on next page)

(continued from previous page)

```

#parentPath = ""

← #tagParentAbsolutePath =/orders/order/innerObject
← #tagAbsolutePath =/orders/order/innerObject/normalPathInInnerObject
    relativeTagPath

← #path = .../defaultName      (only level up)
#parentPath = ""

← #tagParentAbsolutePath =/orders/order
← #tagAbsolutePath =/orders/order/defaultName
    relativeParentPath
#path = defaultName
#parentPath = "../" (only level up)

← #tagParentAbsolutePath =/orders/order
← #tagAbsolutePath =/orders/order/defaultName
#parentPath = "../" (relativeTagPathA)

← #tagParentAbsolutePath =/orders/order
← #tagAbsolutePath =/orders/order/.../defaultName (relative path of parentPath important. path considered
    relativePathFromResult
#path = /orders/order/defaultName
#parentPath = ""

← #tagParentAbsolutePath =/orders/order/defaultName
#tagAbsolutePath =/orders/order

```

tagAbsolutePath and tagParentAbsolutePath:

fieldName	path	parentPath	tagAbsolutePath	tag-ParentAbsolutePath
result	orders/order		order/simpleOrder	/
result	orders/order		order/simpleOrder	/
defaultName	default-Name(default value is field-Name)	order/simpleOrder/defaultName	order/simpleOrder	
tagPathDefined	status	order/simpleOrder/status	order/simpleOrder	
tagPathAnd-ParentPath	status	order/simpleOrder/category/name	order/simpleOrder/category	
innerObject	innerObject	order/simpleOrder/innerObject	order/simpleOrder	
normal-PathInInner-Object	normalPathInInnerObject	order/simpleOrder/innerObject/normalPathInInnerObject	order/simpleOrder/innerObject	
relativeTag-Path	defaultName	order/simpleOrder/defaultName	order/simpleOrder	
relativePar-entPath	defaultName	order/simpleOrder/defaultName	order/simpleOrder	
relativeTag-PathAndPar-entPath	defaultName	order/simpleOrder/..defaultName (relative path of parentPath important. path considered as regex)	order/simpleOrder	
relativePath-FromResult	/orders/order/defaultName	order/simpleOrder/defaultName	order/simpleOrder	

10.2.7 fields

The fields field is used to define the properties of complex objects. Only *Parsing Element* that has complex *type* can have the “fields” field.

The fields field is a map that keys are fieldName of *Parsing Element*, values are string, *Parsing Element* or list of *Parsing Element*

10.2.7.1 Type of Value Definition

The value of the map can be empty, string, *Parsing Element* or array of *Parsing Element*.

Different value definitions create *Parsing Element* with some default values.

Below explain type of value definition and the default values of the *Parsing Element* that it creates.

empty:

fieldName

key of the map.

```

dataType
    string

path
    key of the map (fieldName)

parentPath
    null

string:

fieldName
    key of the map.

dataType
    value of the map

path
    key of the map (fieldName)

parentPath
    null

```

Parsing Element:

```

fieldName
    key of the map.

other fields are can be defined or initialized with default values.

```

Array of Parsing Element:

some fields of objects can be read from the different tag in the source document. By making multiple definitions for one field, the value of different tags can be read.

Example of different type of value definition:

YAML

```

version
result
  type
  path
  fields
    name      # fieldName is "name" and dataType is string and the path is "/name"
    category
    price
      -
      # fieldName is "price" and dataType is "long" and the path is "/price"
      categoryType
      -
      # fieldName is "categoryType" and it is "string" value and the path is "/categoryType" it has extra
        default "foo" # default value a is a string.
        productUnit
      -
      # this field contains two definition. one of that will win depending on the structure of source doc
        path
      -
      # fieldName is "productUnit" and dataType is "long" and the path is "/unit/unit_name"
        default
          'KG'

    path
  -
  # fieldName is "productUnit" and dataType is "long" and the path is "/mainUnit/unit_name"

```

JSON

```
{
  "version": 1.0,
  "result": {
    "type" : "object",
    "path": "/",
    "fields": {
      "name": "",
      "category": "",
      "price": "long",
      "categoryType": {
        "default": "foo"
      },
      "productUnit": [
        { "path": "unit/unit_name",
          "default": " $self.data.categoryType=='foo'? 'LT': 'KG'"
        },
        {
          "path": "mainUnit/unit_name",
        },
        ],
      }
    }
  }
}
```

10.2.8 filter

The filter field determines whether the value of a *Parsing Element* (complex or simple *type* does not matter) is added to the object tree. The filter field is an *expression* that returns true or false.

The following objects are available in Expression Context.

See also:

expression

Name	Data Type	Description	Example
<i>param</i>	Map<string, any>	any <i>params</i> object.	<code>params.dateFormat =='dd.MM.yyyy'</code>
<i>self</i>	Node	current node object that hold data of current complex <i>type</i>	<code>self.data.foo => foo field of current node, self.parent.data.foo => foo field of parent node, self.data.bar.foo => foo field of bar object in current node.</code>
<i>all</i>	Map<string, Any>	Any <i>node</i> that stores all nodes by the “ <i>uniqueName</i> ” of <i>Parsing Element</i>	<code>all.bar.data.foo => foo field of bar node, all.barList.data[0].foo => foo field of first item of barList node</code>
<i>value</i>	string	value of the current tag in <i>source document</i>	<code>value=='Computer', **value.startsWith('bar')**</code>

Examples:

Example 1

YAML

version

```
→ # collect all data that category field is 'Computer'
  fields
    name
    category
```

JSON

```
"version" 1.0
"result"
  "type" "array"
  "path" "/"
  "filter" "$self.data.category=='Computer'"
  "fields"
    "name" "string"
    "category" "string"
```

Example 2

YAML

version

```
  name
  category
  filter      # only assign "category" if "category" is "computer".
```

JSON

```
"version" 1.0
"result"
  "type" "array"
  "path" "/"
  "fields"
    "name" "string"
    "category"
      "filter" "$value=='Computer'"
```

Possible Output Of Example 2

```
"name" "foo"  
"category" "Computer"
```

```
"name" "foo"
```

10.2.9 default

The *default* field holds the value to be assigned to a property by default. The default value is assigned when the *path* does not match the *absolute* path of any tag in the *source document*. If the value of the default field is a string, this value is accepted as the *value* field of the *Default Object*.

See also:

Default Object

Expression

assignment order of the default is from the bottom to up in an object.

Examples

YAML

```
version  
result  
  type  
  path  
  fields  
    name  
      filter  
      default  
        value      # force set name to foo with filter  
        force  
      path  
      category  
      productUnit  
        default          'KG'  
    # default value is expression. this default value is assigned after "categoryType" field assigned.  
    categoryType  
      default "foo"  # default value a is a string.
```

JSON

```
"version" 1.0  
"result"  
  "type" "object"  
  "path" "/"  
  "fields"  
    "name" "string"
```

(continues on next page)

(continued from previous page)

```

"category" "string"
"productUnit"
  "default"  "$self.data.categoryType=='foo'? 'LT': 'KG'"

"categoryType"
  "default"  "foo"

```

10.2.10 transformationCode

transformationCode field refers to the definition of the **transformation** to be used to transform the tag value.

Below definition work as follows:

- value of tag “/country_code” is read from *source document*
- if this value exist in “COUNTRY_CODE_TO_NAME” **transformation** definition, get value that match.
- if not exist, get “DEFAULT” value of “COUNTRY_CODE_TO_NAME” **transformation** definition

YAML

```

version
transformations
  COUNTRY_CODE_TO_NAME
    map
      DEFAULT
      TR
      US

result
  type
  path
  fields
    country
      path
      transformationCode

```

JSON

```

"version"  1.0
"transformations"
  "COUNTRY_CODE_TO_NAME"
    "map"
      "TR"  "Turkey"
      "US"  "United States"
      "DEFAULT"  "Other"

```

(continues on next page)

(continued from previous page)

```
"result"
  "type"  "object"
  "path"   "/"
  "fields"
    "country"
      "path"  "country_code"
      "transformationCode"  "COUNTRY_CODE_TO_NAME"
```

See also:*Transformations*

10.2.11 function

The *function* field refers to the definition of *functions* field to be used for the custom operation. For more detail about how *functions* works, look at *functions* sections.

Below definition work as follows:

- all fields of product are read from *source document*
- When the “/product” tag is closed, the “com.example.InsertProduct” function in the “insertProduct” definition is called.

YAML

```
version
functions
  insertProduct

result
  type
  path
  function
  fields
    name
    price
    image
```

JSON

```
"version"  1.0
"functions"
  "insertProduct"  "com.example.InsertProduct"
```

(continues on next page)

(continued from previous page)

```

"result"
  "type"  "object"
  "path"  "/"
  "function"  "insertProduct"
  "fields"
    "name"  "string"
    "price"  "long"
    "image"  "string"

```

See also:*functions***10.2.12 uniqueName**

When “fieldName” fields of complex *Parsing Element* definitions are the same in the DSM document, these definitions are differentiated by using the “uniqueKey” field. This field is optional. The default value is the value of the “fieldName” field. The uniqueName field may need in very complex document parsing.

Example Case:

In the following DSM document, both the users and the orders objects have a category field and the category field is an object. The *uniqueName* field is used to differentiate the category objects.

YAML

```

version
result
  type
  path
  fields
    users
      type
      fields
        name
        email
        category
          type
          uniqueName
          fields
            categoryName
    order
      type
      fields
        id
        category
          type
          uniqueName

```

(continues on next page)

(continued from previous page)

fields
categoryName

JSON

```
"version" 1
"result"
  "type" "object"
  "path" "/"
  "fields"
    "users"
      "type" "array"
      "fields"
        "name" "string"
        "email" "string"
        "category"
          "type" "object"
          "uniqueName" "userCategory"
          "fields"
            "categoryName" "string"

  "order"
    "type" "object"
    "fields"
      "id" "string"
      "category"
        "type" "object"
        "uniqueName" "orderCategory"
        "fields"
          "categoryName" "string"
```

10.2.13 normalize

The normalize is used to normalize the value of the tag being read. Changes can be made to the raw string value of the tag by using normalize field. The value of this field is an expression.

The following objects are available in Expression Context.

Name	Data Type	Description	Example
<code>params</code>	Map<string, any>	object.	<code>params.dateFormat == 'dd.MM.yyyy'</code>
<code>self</code>	Node	current node object that hold data of current complex type	<code>self.data.foo => foo field of current node, self.parent.data.foo => foo field of parent node, self.data.bar.foo => foo field of bar object in current node.</code>
<code>all</code>	Map<string, Node>	that stores all nodes by the “uniqueName” of Parsing Element Object	<code>all.bar.data.foo => foo field of bar node, all.barList.data[0].foo => foo field of first item of barList node</code>
<code>value</code>	string	raw string value of the current tag in source document	<code>value=='Computer', **value.startsWith('bar')**</code>

See also:

[Expression](#)

10.2.14 xml

The xml field is used to make extra definitions and to change “path” and “type” fields for XML format.

check [XML Object](#) for more detail

See also:

[XML Object](#)

10.2.15 \$ref

\$ref field is used to extends Parsing Element to given fragments. it's value is a Load Time Expression. *fragments* can be extends another *fragments* but can not extends itself. Sometimes we don't need parent properties. To exclude parent properties, define *dataType* as “exclude”. In example bellow category property is excluded.

YAML

```
version
result
  type
  path
  xml
    path  "/Pets/Pet"
$ref
```

(continues on next page)

(continued from previous page)

```

fields
  category
  ↵# import all properties of fragments.pet except category property.
  isPopular

fragments
  tag
    type
    fields
      id
      name
  category
    type
    fields
      id
      name
  pet
    type
    fields
      id
      name
      status
      category
        $ref
      photoUrls
        type
        path
        xml
        path
      tags
        type
        path
        xml
        path
        $ref

```

JSON

```

"version": 1
"result"
  "type": "array"
  "path": "/"
  "xml"
    "path": "/Pets/Pet"

  "$ref": "$fragments.pet"
  "fields"
    "category": "exclude"
    "isPopular": "default $self.data.tags.stream().anyMatch(s->s.name=='Popular')"

```

(continues on next page)

(continued from previous page)

```
"fragments"
  "tag"
    "type"  "object"
    "fields"
      "id"   "int"
      "name"  "string"

  "category"
    "type"  "object"
    "fields"
      "id"   "int"
      "name"  "string"

"pet"
  "type"  "object"
  "fields"
    "id"   "long"
    "name"  "string"
    "status" "string"
    "category"
      "$ref"  "$fragments.category"

  "photoUrls"
    "type"  "array"
    "path"   "photoUrls"
    "xml"
      "path"   "photoUrls/photoUrls"

  "tags"
    "type"  "array"
    "path"   "tags"
    "xml"
      "path"   "tags/tag"

  "$ref"  "$fragments.tag"
```

10.3 Transformation Element Object

Transformation is a very powerful feature that used to map value of a tag from the *source document* to destination document. Transformation Element holds the mapping and how the mapping will be used with `Parsing Element`_s. We can consider, transformation as switch-case in programming language. Every record in the mapping table is a case and DEFAULT record is a default case for switch-case statement.

Fields:

Field Name	Type	Description
map	Map<String, Object>	REQUIRED mapping table from source to destination
only-IfExist	boolean	transform source value only if exist in mapping table. if not exist use as is.
\$ref	string	ref field is used to <i>extends</i> current Transformation Element to another Transformation Element. it is an expression.

YAML

```
version
transformations
  COUNTRY_CODE_TO_NAME
    map
      DEFAULT
      TR
      US
  COUNTRY_CODE_TO_NAME_IF_EXIST
    $ref
    onlyIfExist
```

JSON

```
"version": 1
"transformations":
  "COUNTRY_CODE_TO_NAME"
    "map"
      "DEFAULT": "Other"
      "TR": "Turkey"
      "US": "United States"

  "COUNTRY_CODE_TO_NAME_IF_EXIST"
    "$ref": "$transformations.COUNTRY_CODE_TO_NAME"
    "onlyIfExist": true
```

10.4 Default Object

Default Object determines how the *default* field is assigned.

Fields:

Field Name	Type	Description
<i>value</i>	string	REQUIRED default value that is assigned to current field
<i>force</i>	string	Use the default value, even if the tag specified in the “ <i>path</i> ” field is in the source file.
<i>atStart</i>	string	assign default value at start of tag.

10.4.1 value

REQUIRED it holds default value that is assigned to current field

if the value starts with the “\$” character, it is treated as “expression” and is resolved by expression resolver.

The following objects are available in Expression Context.

Name	Data Type	Description	Example
<i>param</i>	Map<string>	any <i>params</i> object.	<code>params.dateFormat =='dd.MM.yyyy'</code>
<i>self</i>	Node	current node object that hold data of current complex <i>type</i>	<code>self.data.foo => foo field of current node, self.parent.data.foo => foo field of parent node, self.data.bar.foo => foo field of bar object in current node.</code>
<i>all</i>	Map<string>	Map that stores all nodes by the “ <i>fieldName</i> ” of <i>Parsing Element Object</i>	<code>all.bar.data.foo => foo field of bar node, all.barList.data[0].foo => foo field of first item of barList node</code>

10.4.2 force

if it's value is true, it means Use the default value, even if the tag specified in the “*path*” field is in the source file. if force value is true, default value is assigned both start and end of *parentPath*. It is mostly used with filter field or with value in *params*. The default value is false.

10.4.3 atStart

if *atStart* filed is true, default value is assigned at start of the tag. other wise default value is assigned at the end of the tag.

See also:

default

10.5 XML Object

XML Object is used to make extra definitions and to change “*path*” and “*parentPath*” fields for xml format

Fields:

Field Name	Type	Description
<i>path</i>	string	xml specific <i>path</i> definition default value is <i>path</i> field of <i>Parsing Element Object</i>
<i>parent-Path</i>	string	xml specific <i>parentPath</i> definition. default value is <i>parentPath</i> field of <i>Parsing Element Object</i>
<i>at-attribute</i>	boolean	attribute field is indicates that the current <i>Parsing Element Object</i> is an attribute on the tag pointed to by the <i>parentPath</i> field in the xml.

10.5.1 attribute

The attribute field is indicates that the current *Parsing Element* is an attribute on the tag pointed to by the *parentPath* field in the xml.

Examples:

YAML

```
version
result
  type
  path
  xml
    path          # xml specific path definition
    fields
      id
        dataType
        xml
          attribute
        ↵# id field is an attribute that is located at /Pets/Pet tag.
        name
        price
        image
```

JSON

```
"version": 1.0
"result":
  "type": "object"
  "path": "/"
  "xml":
    "path": "/Pets/Pet"

  "fields"
```

(continues on next page)

(continued from previous page)

```
"id"  
    "dataType"  "long"  
    "xml"  
        "attribute"  "true"  
  
    "name"  "string"  
    "price"  "long"  
    "image"  "string"
```

See also:

xml

CHAPTER
ELEVEN

ABSOLUTE PATH

Absolute Path is found by **joining all tag name from top to bottom with “/” character until specified tag.**

Below example is json representation of array of Pet object.

Absolute tag paths are listed below.

```
"id" 1
"category"
  "id" 1
  "name" "Cats"

"name" "PetNameForm"
"photoUrls"
  "url1"
  "url2"
  "url3"

"tags"

  "id" 2
  "name" "New"

  "id" 2
  "name" "Cute"

"status" "sold"
```

Absolute tag paths of all field in above json document are listed below.

Field Name	Absolute Path
	/
Pet:id	/id
Pet:category	/category
Pet:category.id	/category/id
Pet:category.name	/category/name
Pet:name	/name
Pet:photoUrls	/photoUrls
Pet:photoUrls.(item)	/photoUrls
Pet:tags	/tags
Pet:tags.id	/tags/id
Pet.tags.name	/tags/name
Pet.status	/status

Same Example for XML:

```
<Pets>
  <Pet>
    <category>
      <id>1589257917030308320</id>
      <name>Cats</name>
    </category>
    <id>6598053714149410844</id>
    <name>PetNameForm</name>
    <photoUrls>
      <photoUrl>url1</photoUrl>
      <photoUrl>url2</photoUrl>
      <photoUrl>url3</photoUrl>
    </photoUrls>
    <status>sold</status>
    <tags>
      <tag>
        <id>4250197027829930927</id>
        <name>New</name>
      </tag>
      <tag>
        <id>8271965854563266871</id>
        <name>Cute</name>
      </tag>
      <tag>
        <id>3487705188883980239</id>
        <name>Popular</name>
      </tag>
    </tags>
  </Pet>
</Pets>
```

Absolute tag paths of all field in above XML document are listed below.

Field Name	Absolute Path
	/
Pets array	/Pets
Pets array item	/Pets/Pet
Pet:id	//Pets/Pet/id
Pet:category	/Pets/Pet/category
Pet:category.id	/Pets/Pet/category/id
Pet:category.name	/Pets/Pet/category/name
Pet:name	/name
Pet:photoUrls	/Pets/Pet/photoUrls
Pet:photoUrls.(item)	/Pets/Pet/photoUrls
Pet:tags	/Pets/Pet/tags
Pet:id	/Pets/Pet/tags/id
Pet:tags.name	/Pets/Pet/tags/name
Pet.status	/Pets/Pet/status

See also:

path

parentPath

3EXPRESSIONS AND SCRIPTING3EXPRESSIONS AND SCRIPTING

Expressions makes DSM very flexible. Expression allows a value to be filtered, manipulated, modified etc. Expressions can access objects in the expression context and do operations by using these objects.

Expressions can be used at both *source document* parsing time and *DSM document* loading time.

Expressions are resolved by one of Scripting language such a Javascript, Groovy, Apache JEXL or other JSR223 implementations. Expressions must be written with scripting language syntax. Default scripting language is Apache JEXL

See also:

[Apache JEXL](#)

There are two type of expression, Loading Time and Parsing Time expressions.

12.1 Loading	Time	Expression
--------------	------	------------

Loading Time Expression is expressions that is only used during loading of `DSM document`. It allows you to modify structure of DSM document.

Loading Time Expressions are defined in the *\$extends* and or *\$ref* fields. For more detail check *\$extends* and or *\$ref* field.

See also:

[\\$extends](#)

\$ref

The following fields are available in the expression context.

Name	Data Type	Description	Example
<code>params</code>	Map<string, Object>	params object.	<code>params.dateFormat == 'dd.MM.yyyy'</code>

12.1.1 Example

YAML

```

version
params
  rootPath
$extends
  ↴
  ↴ # use "params" object in expression context to get "rootPath" property

```

JSON

```

"version": 1.0
"params"
"rootPath": "/bar/foo/"

"$extends": "/foo/bar/external.json" "$params.rootPath.
  ↴concat('externalWithExpression.json')"

```

12.2 Parsing

Time

Expression

Parsing Time Expression is expressions that is only used during parsing of `source document`. It allows you to change the structure of the output, change the property value, import a specific part of the *source document*, filter by property , transform a property, and almost all operations that can be done with custom coding.

The Parsing Time Expressions can be defined in the *filter*, *default*, and *normalize* fields.

The following objects are available in the expression context.

Name	Data Type	Description	Example
<code>params</code>	Map<String, Object>	Map<String, Object> stores parameters passed to the object.	<code>params.dateFormat == 'dd.MM.yyyy'</code>
<code>all</code>	Map<String, Node>	Map<String, Node> stores all nodes by the “ <i>uniqueName</i> ” of <i>Parsing Element Object</i>	<code>all.bar.data.foo => foo field of bar node, all.barList.data[0].foo => foo field of first item of barList node</code>
<code>self</code>	Node	current node object that hold data of current complex <i>type</i>	<code>self.data.foo => foo field of current node, self.parent.data.foo => foo field of parent node, self.data.bar.foo => foo field of bar object in current node.</code>
<code>value</code>	String (not available in <i>default</i> field)	The raw string value of the current tag in <i>source document</i>	<code>value=='Computer', **value.startsWith('bar')**</code>

See also:

Node_, *default*, *filter*, *normalize*, *\$extends*, *\$ref*

12.2.1 all

Each complex *type* creates a *node_*. The created nodes can be accessed using the “all” object in the expressions. Each node is stored in *all* map with the *uniqueName* of the *Parsing Element* that creates the node.

```
result
  type
  fields
    order
      type
      fields
        state
        createDate
        saleLines
          type
          fields
            product
              type
              fields
                id
                name
                price
            quantity
            unit

  company
    type
    fields
      id
      name
      price
```

for configuration at above following *all* map is created.

```

result
  parent
  data
    order
      ↳ # contains data of the order node
        company
order
  parent
  data
    orderLines
company
  parent
  data
orderLines
  parent
  data   product product.data
  ↳ # data is array. each item contains product data
product
  parent
  data

```

Example usages:

product.parent
is equals orderLine node

product.parent.data
is equals orderLine.data

product.parent.parent
is equals order

product.parent.parent.data
is equals order.data

product.parent.parent.parent
is equals result

order.data.orderLine
is equals orderLine.data

**order.data.orderLine[lastIndex].product
is equals product.data**

12.2.2 self

current node object that hold data of current complex *type*.

Example usages:

self.parent
parent node

self.data.foo
foo field of current object

self.data[0]
First element of current array

12.2.3 Example

YAML

```

version
result
  type
  path
  fields
    name
      filter
        # filter expression.
        default
          value      # force set name to foo with filter
          force
        path
      category
        type
        fields
          id
          name
          default
            # default value is expression.
        categoryType
          default
        ...
        ...
        # default value is expression. and its is equivalent of expression in
        productUnit
          default
            'KG
        '# default value is expression.
        categoryType
          default "foo"   # default value a is a string.

```

JSON

```
{  
    "version": 1.0,  
    "result":{  
        "type":object,  
        "path":"/",  
        "fields":{  
            "name":string,  
            "category":{  
                "id": int,  
                "name": {  
                    "default": "self.parent.data.  
↳categoryType=='foo'? 'Foo':'Bar'",  
                },  
                "categoryType": {  
                    "default": "default: all.data.  
↳categoryType=='foo'? 'Foo':'Bar'",  
                }  
            },  
            "productUnit":{  
                "default": " $self.data.categoryType=='foo  
↳'? 'LT': 'KG'"  
            },  
            "categoryType":{  
                "default": "foo"  
            }  
        }  
    }  
}
```

MERGE OF DSM DOCUMENT

DSM document can extends to another DSM document by using **\$extends** field.

Parsing Element can extends to another Parsing Element by using **\$ref** field.

DSM documents and Parsing Elements are merged with each other.

Before going to explain merge process lets make some definition.

source:

DSM Document or Parsing Element that we want to extend to another.

target:

DSM Document or Parsing Element that we want to extend to.

Merge process work as follows:

for every field of target do followings:

1. if field not exist in source, copy value of target to source.
2. if field exist in source do followings
 - 2.1. if dataType of fields is different then skip this field.
 - 2.2. if dataType of fields is same then do followings
 - 2.2.1. if dataType is simpleDataType (string,number) then skip this field (do not copy target to source)
 - 2.2.2. if dataType is array then add target values to start of the source values

2.2.3. if dataType is map then start Merge process for those two map.

Example merge process of DSM documents:
external DSM Document:(external.yaml)

```
version
params
  dateFormat
  rootPath
  acceptedCountryCode    TR US FR
transformations
  COUNTRY_CODE_TO_NAME
    map
      DEFAULT
      TR
      US
result
  fields
    id
    name
    price
```

current DSM Document:

```
version
$extends
  ~# resolve expression
params
  rootPath
  acceptedCountryCode    UK
transformations
  COUNTRY_CODE_TO_NAME
    map
      UK
result
  type
  path
  fields
    category
```

After merge process following configuration will take effect:

```
version
$extends
params
    dateFormat
        ↳ # (rule 1) imported from external document
    rootPath
        ↳ # (rule 2.2.1) overwritten by current DSM document
    acceptedCountryCode    TR US FR UK ↳
        ↳ #(rule 2.2.2) external list element added to start off current list ↳
transformations
    ↳ #(rule 2.2.3) transformations field exist in both source and target ↳
        COUNTRY_CODE_TO_NAME    #(rule 2.2.3)
            ↳ map
                ↳ UK
                    ↳ # only exist in current DSM document
                    ↳ DEFAULT
                ↳ TR
                ↳ # (rule 1) imported from external document
                ↳ US
                ↳ # (rule 1) imported from external document
            ↳ # (rule 1) imported from external document

result
    type          # exist only current DSM document
    path
    fields
        category      # exist only current DSM document
        id
        name          # imported from external document
        price
```

PROPERTY ASSIGNMENT ORDER

The property assignment order is very important for the correct operation of the expressions in the filter field and in the default field

Referencing a not existing field in “self.data” can cause
NullPointerException.

DSM reads *source document* top to bottom in one pass as a stream.

Once it reads a tag *source document*, it checks whether *absolute path* of the tag match with **tagAbsolutePath_** or **taParentAbsolutePath_** of any of *Parsing Element* if Parsing Element founds, value of tag is assigned according to *Parsing Element* definitions.

The Property assignment work as follows:

let's name the tag that is pointed by *path* as current tag and the tag that is pointed by *parentPath* as parent tag

The property is assigned when current tag is closed except *attribute properties* for the XML document. The *attribute* properties is assigned at start of parent tag by reading attribute value of parent tag

Order of the property assignment as follows:

- the closing of ‘**current tag**’ _ is near to the document header(starting of parent tag” for attribute)
- deeper ‘**current tag**’ _
- **Parsing Element definition close to the document header.(assignment start from top to bottom)**

The **default** value of a property is assigned when current tag not exist in source document and parent tag” is closed(for all property, include **attribute**).

default value is assigned only once except **force** field is true. if **force** field is true default value is assigned at both start and close of parent tag

Order of the default value of property assignment as follows:

- assure the property is not assigned or force field is true
- the closing of `parent tag` _is near to the document header.
- deeper **parent tag**
- Parsing Element definition far to the document header.(assignment start bottom to top)

Example:

```
<Pets>
  <Pet>
    <category>
      <id>1</id>
      <name>Cats</name>
    </category>
    <id>6598053714149410844</id>
    <name>Van Kedisi</name>
    <photoUrls>
      <photoUrl>url1</photoUrl>
      <photoUrl>url2</photoUrl>
      <photoUrl>url3</photoUrl>
    </photoUrls>
    <status>sold</status>
    <tags>
      <tag>
        <id>1</id>
        <name>New</name>
      </tag>
      <tag>
        <id>2</id>
        <name>Cute</name>
      </tag>
      <tag>
        <id>3</id>
        <name>Popular</name>
      </tag>
    </tags>
  </Pet>
</Pets>
```

```
result
  type
  path
  xml
    path  "/Pets/Pet"
  fields
```

```
  status
  isPopular
```

→

```
  category
    type
    fields
      name
      id
  photoUrls
    type
    path
    xml
      path
  tags
    type
    path
    xml
      path
  fields
```

DSM read document top to bottom.

- it finds **/Pets/Pet** *absolute* path that match with result Parsing Element. Then create a array and put first item into the array.

```
result=[{}]
```

- it finds /Pets/Pet/category match with category Parsing Element. then it create a object and assign it to category property

```
result=[{
  "category": {}
}]
```

- it finds /Pets/Pet/category/id match with category.id Parsing Element. then it assign it to id property of category object.

```
result=[{
  "category": {
    "id": 3
  }
}]
```

- it finds /Pets/Pet/category/name match with category.name Parsing Element. then the value is assigned

```
result=[{
  "category": {
    "id": 3,
    "name": "Cats"
  }
}]
```

- it finds /Pets/Pet/id match with id then the value is assigned

```
result=[{
  "category": {
    "id": 3,
    "name": "Cats"
  }
  "id":1
}]
```

- it finds /Pets/Pet/name match with name then the value is assigned

```
result=[{
  "category": {
    "id": 3,
    "name": "Cats"
  },
  "id":1,
  "name": "Van Kedisi",
}]
```

- it finds /Pets/Pet/photoUrls/photoUrl match with photoUrls Parsing Element then the new array is created and assigned

```
result=[{
  "category": {
    "id": 3,
    "name": "Cats"
  },
  "id":1,
  "name": "Van Kedisi",
  "photoUrls": []
}]
```

- it finds /Pets/Pet/photoUrls/photoUrl match with photoUrls then the value of photoUrls is assigned

```
result=[{
  "category": {
    "id": 3,
    "name": "Cats"
  },
  "id": 1,
  "name": "Van Kedisi",
  "photoUrls": ["url1", "url2", "url3"]
}]
```

after reading all fields under /Pets/Pet path following result generated.

```
result=[{
  "category": {
    "id": 3,
    "name": "Cats"
  },
  "id": 1,
  "name": "Van Kedisi",
  "photoUrls": ["url1", "url2", "url3"],
  "status": "sold",
  "tags": [
    {
      "id": 1,
      "name": "New"
    },
    {
      "id": 1,
      "name": "Cute"
    },
    {
      "id": 1,
      "name": "Popular"
    }
  ]
}]
```

- it can't find /Pets/Pet/isPopular but isPopular property has default value. When /Pets/Pet (parent tag) tag is closed then its expression is evaluated. The result of expression is assigned to isPopular property.

```
result=[{
  "category": {
    "id": 3,
    "name": "Cats"
  },
  "id": 1,
  "name": "Van Kedisi",
  "photoUrls": ["url1", "url2", "url3"],
  "status": "sold",
  "tags": [
    {
      "id": 1,
      "name": "New"
    },
    {
      "id": 1,
      "name": "Cute"
    },
    {
      "id": 1,
      "name": "Popular"
    }
  ],
  "isPopular": true
}]
```

CHAPTER
FIFTEEN

INDICES AND TABLES

- **genindex**
- **modindex**
- **search**